

1. GENERAL INFORMATION

1.1 Dealer Information

Dealer Name
Date (MM/DD/YY)
Address
City
Province/State
Postal Code
Email

1.2 Shipping Information

Contact
Phone
Address
City
Province/State
Postal Code/ZIP

1.3 Project

Purchase Order#
Contact
Phone
Ship To
City
Province/State
Postal Code

1.4 Type of Delivery

☐ Pick-up at Terminal ☐ Onsite Forklift
☐ Loading Dock ☐ Flatbed and Forklift
☐ Liftgate - Ground Delivery ☐ Pick-up AMG Facility

STANDARD INCLUSIONS

Each Vista VPL Kit includes the following:

Model:	Hercules 750	Safety Features:	Obstruction sensor
Dimension:	36W x 54"D x 42" H		underpan
Lifting height:	64"		limit switches
Tower height:	92"		emergency stop
Capacity:	750 lbs		emergency lowering
Speed:	12 fpm		slip-resistant floor
Color:	Gray (RAL 7047)		key lock controls
Motor:	1 hp, 24VDC motor		brass safety nut
Power supply:	120v/ 20A (2 x 12v gel batteries)		automatic folding ramp



2. CUSTOM CONFIGURATION

QUICK SHIP MODELS

*Quick Ship units are available on these models only.
These units will be available to ship in 24-48 hours.*

☐ NANO VERTICAL PLATFORM LIFT*
☐ RESIDENTIAL VISTA 64"
☐ COMMERCIAL VISTA 64***

* See page 6 for details.

** Includes 2 Gates and 2 Call Stations.

CUSTOM CONFIGURATION

☐ REGULAR VISTA 64"

2.1 Travel Height

EXACT TRAVEL HEIGHT IN INCHES: _____

NOTE - MEASURE FROM
TOP LANDING TO FLOOR/
PIT BOTTOM

☐ 44" MAXIMUM LIFT HEIGHT (TOWER 72")
☐ 64" MAXIMUM LIFT HEIGHT (TOWER 92")
☐ 78" MAXIMUM LIFT HEIGHT (TOWER 108")
☐ 98" MAXIMUM LIFT HEIGHT (TOWER 126")
☐ 115" MAXIMUM LIFT HEIGHT (TOWER 158")
☐ 130" MAXIMUM LIFT HEIGHT (TOWER 158")
☐ 160" MAXIMUM LIFT HEIGHT (TOWER 190")

HERCULES 750

VERTICAL PLATFORM LIFT

2. PLATFORM CONFIGURATION CONTINUED

2.2 Application

- ☐ RESIDENTIAL
- ☐ COMMERCIAL

2.3 Unit Power

- ☐ AC - 120v / 20A (POWER TRANSFORMER)
- ☐ DC - 24v / 15A (TWO 12v BATTERIES)

2.4 Cabin Height

- ☐ 42" GUARD PANELS
- ☐ PLATFORM CANOPY
- ☐ ENCLOSED CABIN 80" HIGH

2.5 Color


- ☐ ATLAS GRAY (STANDARD)
- ☐ CUSTOM COLOR (RAL UNIVERSAL CHART)
- ☐ STAINLESS STEEL

2.6 Load Capacity


- ☐ 750 LBS CAPACITY (STANDARD)
- ☐ 1000 LBS CAPACITY

2.7 Cab Configuration (Check One)

Tower on LEFT



Tower on RIGHT



2.8.1 Installation Type

- ☐ UNENCLOSED
- ☐ HOISTWAY / ENCLOSURE

2.8.2

- ☐ PIT MOUNTED
- ☐ CONCRETE SLAB

2.9 Wing Walls

- ☐ 64" TRAVEL (1625 mm)
- ☐ 78" TRAVEL (1981 mm)
- ☐ 98" TRAVEL (2489 mm)
- ☐ 115" TRAVEL (2921 mm)
- ☐ 130" TRAVEL (3302 mm)
- ☐ 160" TRAVEL (4064 mm)

2.10 Dimensions

- ☐ 34" X 54" (864 mm X 1372 mm)
- ☐ 34" X 60" (864 mm X 1524mm)
- ☐ 36" X 54" (915 mm X 1372 mm)
- ☐ 36" X 60" (915 mm X 1524 mm)

- ☐ CUSTOM SIZE

CUSTOM SIZE IN INCHES: _____ WIDTH X _____ LENGTH
* CHOOSE BETWEEN 30" to 44" WIDTH X 46" to 66" LENGTH*


HERCULES 750

VERTICAL PLATFORM LIFT

3. CALL STATIONS

3.1 Call Station Options (Please select your configuration)


☐ CALL STATIONS (FLUSH MOUNTED, SURFACE MOUNTED, CALL POST, TOP GATE FRAME MOUNTED)



FLUSH MOUNTED

BOTTOM

TOP

☐☐

SURFACE MOUNTED

BOTTOM


TOP

☐☐

CALL POST

BOTTOM

TOP

☐☐

TOP GATE FRAME MOUNTED

TOP ONLY

☐

3.2 Number of Stops

☐ TWO STOPS

☐ THREE STOPS

3.3 Controller Options

☐ STANDARD ROCKER SWITCH

☐ 60MM CALL STATION BUTTON

☐ 60MM COP BUTTON

☐ JOYSTICK

☐ ADDITIONAL COP (ONE ON EACH SIDE)

☐ LIGHTED BUTTONS (COP)

4. GATES AND DOORS

4.1 Lower Landing Entrance (Interlock Included)

4.1.1 Platform Gates

CHOOSE AN ORIENTATION:

* WHEN FACING THE GATE/DOOR
FROM OUTSIDE OF THE PLATFORM *

☐

LEFT

☐

RIGHT

☐ 34" OR 36" WIDTH X 42" HEIGHT

☐ 32", 38", 40", 42" WIDTH X 42" HEIGHT

ADDITIONAL OPTIONS

☐ OPTIONAL LEXAN GATE UPGRADE

☐ INTERLOCK ONLY

4.1.2 Doors

☐

36" WOOD INTERIOR

☐

36" FIRE RATED

☐

36" EXTERIOR

☐

36" POLYCARBONATE

☐

38-42" WOOD INTERIOR

☐

38-42" FIRE RATED

☐

38-42" EXTERIOR

☐

38-42" POLYCARBONATE

HERCULES 750

VERTICAL PLATFORM LIFT

4. GATES AND DOORS CONTINUED

4.2 Upper Landing Entrance (Interlock Included)

4.2.1 Top Gates

CHOOSE AN ORIENTATION:

* WHEN FACING THE GATE/DOOR
FROM OUTSIDE OF THE PLATFORM *

☐ LEFT ☐ RIGHT

- ☐ 34" OR 36" WIDTH X 42" HEIGHT
☐ 32", 38", 40", 42" WIDTH X 42" HEIGHT

ADDITIONAL OPTIONS

- ☐ OPTIONAL LEXAN GATE UPGRADE
☐ INTERLOCK ONLY

4.2.2 Doors

- ☐ 36" WOOD INTERIOR
☐ 36" FIRE RATED
☐ 36" EXTERIOR
☐ 36" POLYCARBONATE
☐ 38-42" WOOD INTERIOR
☐ 38-42" FIRE RATED
☐ 38-42" EXTERIOR
☐ 38-42" POLYCARBONATE

5. AUTOMATIC GATE AND DOOR OPENERS

	QUANTITY	TOTAL
☐ DOOR CLOSER (REQUIRED IF NO DOOR OPERATOR INSTALLED)		
☐ AUTOMATIC GATE OPERATOR (RESIDENTIAL ONLY)		
☐ AUTOMATIC DOOR OPENER (RESIDENTIAL)		
☐ AUTOMATIC DOOR OPENER (COMMERCIAL)		

6. ADDITIONAL OPTIONS

☐ GRAB RAIL (INCLUDED IN COMMERCIAL KIT)		
☐ ANTI-CORROSION KIT (FOR INSTALLATIONS NEAR POOLS, WATER)		
☐ FOLDING SEAT + HARDWARE (INSTALLATION NOT INCLUDED)		
☐ SUPPORT BACK BRACKETS (FIXED ONTO CONCRETE SLAB)		
☐ TRIANGLE SUPPORT BRACKETS (FIXED TO UPPER LANDING) - INCLUDED WITH 115" - 130" - 160" MODELS		
☐ HANDS-FREE PHONE		
☐ STATIONARY RAMP 40" x 36" x 3"		
☐ TOUCH-UP PAINT	QUANTITY	TOTAL


HERCULES 750

VERTICAL PLATFORM LIFT

7. HERCULES PORTABLE

- ☐ TRAVEL 44" - 36" X 54"
- ☐ TRAVEL 44" - 36" X 60"
- ☐ TRAVEL 64" - 36" X 54"
- ☐ TRAVEL 64" - 36" X 60"


INCLUDES: 2 PLATFORM GATES, 2 CALL STATIONS, GRAB RAIL, FOLDING RAMP



8. HERCULES ENCLOSURE

8.1 Travel

- ☐ TRAVEL 0" to 44"
- ☐ TRAVEL 0" to 64"
- ☐ TRAVEL 0" to 78"
- ☐ TRAVEL 0" to 98"
- ☐ TRAVEL 0" to 115"
- ☐ TRAVEL 0" to 130"
- ☐ TRAVEL 0" to 160"



8.2 Options

- ☐ ROOF AND VENTILATION

	QUANTITY	TOTAL
☐ TINTED LEXAN (PER INCH OF TRAVEL)		
☐ GLASS ENCLOSURE (PER INCH OF TRAVEL)		